




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : G06F 9/46		A1	(11) International Publication Number: WO 99/03036
			(43) International Publication Date: 21 January 1999 (21.01.99)
(21) International Application Number: PCT/EP98/04275 (22) International Filing Date: 9 July 1998 (09.07.98) (30) Priority Data: 60/052,350 11 July 1997 (11.07.97) US (71) Applicant: TELEFONAKTIEBOLAGET LM ERICSSON (publ) [SE/SE]; S-126 25 Stockholm (SE). (72) Inventor: JOHANSSON, Björn; Drevkarlstigen 2, S-192 53 Sollentuna (SE). (74) Agents: VON FISCHERN, Bernhard et al.; Hoffmann . Eitle, Arabellastrasse 4, D-81925 Munich (DE).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.	

(54) Title: REMOTE PROCEDURE CALL TRANSLATION

(57) Abstract

A remote procedure call (RPC) client (30) operates on a first level language platform and forwards a request for a RPC service to a second level language platform. The RPC client (30) includes an RPC service table (52) having a plurality of keys (60) stored therein as well as translation description memory (51) having a plurality of translation descriptions. When an applications program (32) on the first level language platform requests an RPC service of the second level language platform, a main interface process (50) of the RPC client obtains an appropriate one of the keys (60) from the RPC service table (52) and uses the appropriate one of the keys to select an appropriate one of the plurality of translation descriptions. A translation engine (54) uses the appropriate one of the plurality of translation descriptions to prepare a protocol formatted message for forwarding to the second level language platform. The protocol formatted message includes the appropriate one of the keys. A response from the RPC service of the second level language platform also includes a key which is used by the RPC client (30) to translate the response back to the first level language.


 received
 NFOA 9/14/04

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

REMOTE PROCEDURE CALL TRANSLATION

BACKGROUND

1. Field of Invention

This invention pertains to translation between data
5 structures operative on differing but communicating
computerized platforms.

2. Related Art and Other Considerations

10 Many computerized products actually require several computers
or computer systems to accomplish specified functions. The
constituent computer systems of such a product are typically
each considered to be a "platform", and are connected by a
physical communications link such as a cable. Each platform
15 executes software in the form of sets of instructions coded
in accordance with a particular software or programming
language.

The platforms are typically configured for differing
20 purposes. For example, software executed by one platform may
comprise hardware "drivers" for controlling actual hardware
equipment, while the software executed by another platform
may be managerial or administrative. An example is a
telecommunications access product, in which one platform
25 controls a piece of telecommunications hardware while another
platform performs administrative or supervisory functions.

In some situations the software or programming language for one platform is more "high level" than the programming language for the other platform. By "high level" is meant that the programming language is more sophisticated, more complex, or more specialized than the programming language of the other platform. Typically each platform has one or more data structures in its programming language. Despite the differing levels of language, the two platforms must nevertheless communicate, e.g., data from the differing data structures must be passed back and forth between the platforms. Typically there is a predetermined protocol involved as an interface between e.g., the data structures of the two platforms.

One context requiring translation is required when one platform accesses a different-level data structure running on another platform by use of a remote procedure call, known as an "RPC", to a remote procedure service. Remote procedure calls are described, for example, in U.S. Patent 5,568,723; U.S. Patent 5,515,508; and U.S. Patent 5,307,490, all of which are incorporated herein by reference. In such context, remote procedure call (RPC) libraries can be employed for translation. These RPC libraries use standard functions to pack and unpack simple data types into/from the protocol.

Unfortunately, such PRC libraries are typically accessible only when using more common programming languages, and are often not as available for less frequently utilized programming languages. For the less common programming languages, the cost of developing a PRC library can be quite high.

Another approach for translation using remote procedure calls (RPCs) is preparation of a proprietary object which interfaces with the remote procedure service and which provides packaging and unpackaging services. Implementation
5 of such an approach also has considerable cost.

What is needed, therefore, and an object of the present invention, is a simple and flexible translation between data structures used in languages of differing levels.

10

SUMMARY

A remote procedure call (RPC) client operates on a first level language platform and forwards a request for a RPC
15 service to a second level language platform. The RPC client includes a RPC service table having a plurality of keys stored therein as well as translation description memory having a plurality of translation descriptions. When an applications program on the first level language platform
20 requests an RPC service of the second level language platform, a main interface process of the RPC client obtains an appropriate one of the keys from the RPC service table and uses the appropriate one of the keys to select an appropriate one of the plurality of translation descriptions. A
25 translation engine uses the appropriate one of the plurality of translation descriptions to prepare a protocol formatted message for forwarding to the second level language platform. The protocol formatted message includes the appropriate one of the keys. A response from the RPC service of the second
30 level language platform also includes a key which is used by the RPC client to translate the response back to the first

level language.

BRIEF DESCRIPTION OF THE DRAWINGS

5 The foregoing and other objects, features, and advantages of the invention will be apparent from the following more particular description of preferred embodiments as illustrated in the accompanying drawings in which reference characters refer to the same parts throughout the various
10 views. The drawings are not necessarily to scale, emphasis instead being placed upon illustrating the principles of the invention.

Fig. 1 is a schematic view of two differing computerized
15 platforms, one of the platforms including a PRC server and the other of the platforms including a RPC client.

Fig. 2 is a schematic view of an embodiment of the RPC client of Fig. 1.

20

DETAILED DESCRIPTION OF THE DRAWINGS

In the following description, for purposes of explanation and not limitation, specific details are set forth such as
25 particular architectures, interfaces, techniques, etc. in order to provide a thorough understanding of the present invention. However, it will be apparent to those skilled in the art that the present invention may be practiced in other embodiments that depart from these specific details. In
30 other instances, detailed descriptions of well known devices, circuits, and methods are omitted so as not to obscure the

description of the present invention with unnecessary detail.

Fig. 1 shows two computerized platforms, particularly platform B and platform A. Platform B, known as the lower level language platform, has a RPC server 20 and a plurality of RPC services 22A - 22N. Platform A, known as the higher level language platform, has a RPC client 30 and a plurality of applications 32A - 32C (three such applications being shown as an example). RPC server 20 and RPC client 30 are connected by communications link 40 for which there is a protocol P for translation between platform A and platform B. Between RPC client 30 and applications 32A - 32C is an RPC service interface 42.

An example of the lower level language executing on platform B can be an imperative language such as the "C" programming language, while a higher level language such as Prolog, Lisp, or variants thereof may be executing on platform A. PRC server 20 of platform B is included in software executing on platform B. PRC server 20 dispatches RPC requests received from platform A to different ones of the PRC services 22.

PRC client 30 of the present invention performs a simple and flexible translation of the higher level language data structures employed on platform A towards protocol P. In addition, PRC client 30 provides a transparent interface to other applications executing on platform A.

Fig. 2 shows PRC client 30 as including main interface process 50; translation description memory 51; RPC service table 52; translation engine 54; an add/remove/lookup service

56; and, communication interface 58. Communication interface 58 is connected to communications link 40.

- RPC service table 52 is stored in a memory (e.g., RAM) and has, at corresponding addresses, a plurality of RPC items represented by items 60A - 60K. Each item has as one of its fields an RPC service identifier as a key, e.g., keys 62A - 62K being shown in Fig. 2.
- 10 In accordance with the present invention, one of the applications 32 running on platform A, known as the calling application, requests one of the RPC services 22 executing on platform B. The request, in the form of a remote procedure call, can include procedure arguments, e.g., parameters to be
- 15 passed to the RPC service 22 for utilization thereby in performance of the PRC service. The request by the calling application 32 is made over interface 42 to main interface process 50 of platform A.
- 20 Dependent on which of the particular applications 32 is the calling application, and the nature of the request (e.g., the particular RPC service to be performed), main interface process 50 uses add/remove/lookup service 56 to consult RPC service table 52 in order to locate an appropriate one of the
- 25 items 60 in RPC service table 52 for the RPC service request. Once the appropriate item 60 is located in RPC service table 52, a key 62 is extracted therefrom. The extracted key 62 is then given to main interface process 50, which retrieves a translation description based on this key from translation
- 30 description memory 51. Typically, translation description memory has a different translation description for each key.

In essence, each translation description includes instructions or criteria for enabling a translation from the higher level language of platform A to protocol P.

5 Upon retrieval of the translation description from memory 51, the translation description and arguments for the PRC service are sent by main interface process 50 to translation engine 54. Translation engine 54 uses the translation description and RPC arguments of the higher level language of platform A
10 to prepare a protocol P-formatted message. The key 62 is also included in the protocol P-formatted message. The protocol P-formatted message is applied via communications interface 58 to link 40 for transmission to RPC server 20 of platform B.

15

At platform B, the protocol P-formatted message is processed, interpreted by RPC server 20, and forwarded to a particular one of the RPC services in accordance with the request from the calling applications program 32. The particular RPC
20 service which was invoked by the calling applications program prepares a response which is forwarded in a protocol P-formatted response message over link 40 to platform A. The forwarded response also includes a key 62, which in some cases can be the same key which was transmitted from platform
25 A to platform B in connection with the RPC service request.

The protocol P-formatted response message received on link 40 is received at communication interface 58 where it is processed and forwarded to main interface process 50. At
30 main interface process 50, the key 62 included in the response message is extracted. Based on the extracted key

62, a suitable translation description is obtained from translation description memory 51. The translation description and the P-formatted response message are then forwarded to translation engine 54 for translation back to the higher level language data structure utilized by the calling application. After preparation of the translation in the higher level language, the translated response is sent by main interface process 50 to the calling application 32, i.e., the application that requested the RPC service.

RPC service table 52 is dynamically configurable so that new items can be added, old items removed, or existing items retrieved and/or modified, e.g., in accordance with the particular services 22 provided on platform B.

Add/remove/lookup service 56 facilitates these operations, and communicates over interface 42 with the applications programs 32.

The present invention provides a cost effective implementation of RPC service where different platforms pose translation problems for the communication protocol. The present invention is particularly suitable for higher level language implementations and provides straightforward translations of symbols, lists, and complex data structures.

While the invention has been particularly shown and described with reference to the preferred embodiments thereof, it will be understood by those skilled in the art that various alterations in form and detail may be made therein without departing from the spirit and scope of the invention. The embodiments of the invention in which an exclusive

property or privilege is claimed are defined as follows:

CLAIMS

1. A remote procedure call (RPC) client operating on a first
level language platform and which forwards a request for a
5 RPC service to a second level language platform, the client
comprising:

a RPC service table having a plurality of keys stored
therein;

10

a translation description memory having a plurality of
translation descriptions stored therein;

a translation engine;

15

a main interface process which, based on the request for the
RPC service, obtains an appropriate one of the keys from the
RPC service table and uses the appropriate one of the keys to
select an appropriate one of the plurality of translation

20

descriptions; and

wherein the translation engine uses the appropriate one of
the plurality of translation descriptions to prepare a
protocol formatted message for forwarding to the second level
25 language platform, the protocol formatted message including
the appropriate one of the keys.

2. The apparatus of claim 1, wherein the RPC service table is
dynamically configurable for selective inclusion and removal
30 of RPC services.

1/2




FIG. 1

2/2




FIG. 2

INTERNATIONAL SEARCH REPORT

Int. l. Application No
PCT/EP 98/04275

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 G06F9/46

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DAVE A ET AL: "PROXIES, APPLICATION INTERFACE, AND DISTRIBUTED SYSTEMS" PROCEEDINGS INTERNATIONAL WORKSHOP ON OBJECT ORIENTATION IN OPERATING SYSTEMS, 24 September 1992, pages 212-220, XP002009478 see abstract see page 217, left-hand column, last paragraph - page 218, right-hand column, paragraph 1	1,2
Y	EP 0 414 624 A (IBM) 27 February 1991 see the whole document --- -/-	1,2

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"Z" document member of the same patent family

Date of the actual completion of the international search

2 November 1998

Date of mailing of the international search report

12/11/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl
Fax: (+31-70) 340-3016

Authorized officer

Fonderson, A

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 98/04275

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	HERRICK J. JOHNSON: "Each piece in its place" UNIX REVIEW, vol. 5, no. 5, June 1987, pages 66-75, XP002082766 see page 73, right-hand column, line 8 - page 74, right-hand column, line 46	1,2
A	WO 97 08616 A (BELL COMMUNICATIONS RES) 6 March 1997 see the whole document	1,2
A	NARENDER V R ET AL: "DYNAMIC RPC FOR EXTENSIBILITY" PROCEEDINGS OF THE ANNUAL INTERNATIONAL PHOENIX CONFERENCE ON COMPUTERS AND COMMUNICATIONS, SCOTTSDALE, APR. 1 - 3, 1992, no. CONF. 11, 1 April 1992, pages 93-100, XP000310598 INSTITUTE OF ELECTRICAL AND ELECTRONICS ENGINEERS see the whole document	1,2

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 98/04275

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0414624 A	27-02-1991	DE 69029441 D	30-01-1997
		DE 69029441 T	12-06-1997
		JP 2677343 B	17-11-1997
		JP 3090953 A	16-04-1991
		US 5218699 A	08-06-1993
WO 9708616 A	06-03-1997	NONE	